

WHAT IS CLAIMED IS:

1. An image displaying device comprising:
 - a display unit which displays a cursor and at least one
5 button;
 - an input unit for moving the cursor and for selecting
said at least one button; and
 - a controller for controlling the display unit and the
input unit,
 - 10 wherein the input unit comprises an operating part
operated by an operator, at least one position sensor that
detects an operation state of the operating part, and at
least one actuator that applies a specific external force to
the operating part,
 - 15 wherein the controller calculates the operated distance
and the operated direction of the operating part based on at
least one position signal output from said at least one
position sensor, and moves the cursor based on the calculated
operated distance and the calculated operated direction of
20 the operating part, and
 - wherein, when a display screen of the display unit is
switched, said at least one actuator is driven to move the
cursor to a default position set in the switched display
screen at a predetermined moving rate.
 - 25
2. The image displaying device according to Claim 1,
wherein, during an operation of the operating part, when the
cursor is moved to an area having a predetermined radius from

the center of said at least one button, said at least one actuator is driven to pull the cursor to the center of said at least one button.

5 3. The image displaying device according to Claim 2, wherein the predetermined moving rate is lower than a moving rate of the cursor for pulling the cursor towards the center of said at least one button.

10 4. The image displaying device according to Claim 1, wherein the switched display screen includes a plurality of the default positions so that when the display screen of the display unit is switched, the cursor is moved to the nearest one of the default positions.

15 5. The image displaying device according to Claim 2, wherein, when the cursor is pulled to the center of said at least one button, the controller drives said at least one actuator to impart specific force feedback, which corresponds
20 to said at least one button, to the operating part.